



ALLNET ALL-SG8950PM

Layer 2+ FULL Management 24 Port Giga PoE Current Sharing Switch IEEE802.3at/af

- *48x 10/100/1000Base-T PoE + 2x 10G Gigabit SFP+*
- *400W Current Sharing PoE*
- *IEEE 802.3at PoE, bis zu 30W pro Port*
- *Layer 2 + Full Management Software Features*
- *4K VLAN, 8 queues QoS, Advanced VLANs*
- *MSTP, LLDP, SFlow, 802.1X, TACAS+, ACL*
- *IPv4/IPv6 dual protocol*

Introduction

The switch is 48-port 10/100/1000Base-T + 2 10 Gigabit SFP+ Ports Rack-mount L2+ Full Management Network Switch that is designed for medium or large network environment to strengthen its network connection. The switch supports 136G non-blocking switch fabric, the 48 gigabit ports and 2 10G uplink ports can transmit and receive data traffic without any loss. The EEE feature reduces the power consumption when there is no traffic forwarding even port is still connected. The switch also supports Layer 2+ full management software features. These features are powerful to provide network control, management, monitor and security feature requests. Including rack-mount brackets, the 19" size fits into your rack environment. It is a superb choice to boost your network with better performance and efficiency.

Art. Nr.: 122261



Current Sharing PoE

ALL-SG8926PM equipped with Current Sharing technology to support maximum 500W power consumption for PoE power. There are 2 power modules inside, they work together to provide 500W PoE power to the front 24 PSE ports. Once one of the power modules is failure, the other power module can backup and continuously deliver 250W PoE power. Once the PD clients request higher than 250W power, the user can configure the priority value for the PSE ports, the switch delivers power to the higher priority ports first.

2x 10G Gigabit SFP+ Open Slots

The switch equips with 2 10G SFP+ open slots as the uplink ports, the 10G uplink design provides an excellent solution for expanding your network from 1G to 10G. By 10G speed, this product provides high flexibility and high bandwidth connectivity to another 10G switch or the Servers, Workstations and other attached devices which support 10G interfaces. The user can also aggregate the 10G ports as Trunk group to enlarge the bandwidth.

Full Layer 2+ Management Features

The switch includes full Layer 2+ Management features. The software set includes up to 4K 802.1Q VLAN and advanced Protocol VLAN, Private VLAN, MVR...features. There are 8 physical queues Quality of Service, IPv4/v6 Multicast filtering, Rapid Spanning Tree protocol to avoid network loop, Multiple Spanning Tree Protocol to integrate VLAN and Spanning Tree, LACP, LLDP; sFlow, port mirroring, cable diagnostic and advanced Network Security features. It also provides Console CLI for out of band management and SNMP, Web GUI for in band Management.

Advanced Security

The switch supports advanced security features. For switch management, there are secured HTTPS and SSH, the login password, configuration packets are secured. The port binding allows to bind specific MAC address to the port, only the MAC has the privilege to access the network. The 802.1X port based Access Control, every user should be authorized first when they want to access the network. AAA is the short of the Authentication, Authorization and Accounting with RADIUS, TACAS+ server. Layer 2+ Access Control List allows user to define the access privilege based on IP, MAC, Port number, and etc.



Technical Specifications

Standards:	Ethernet: IEEE 802.3, 802.3u, 802.3ab, 802.3ae IEEE 802.3az Energy Efficient Ethernet (EEE) Protocol: IEEE 802.3x - Flow Control, IEEE 802.1Q – VLAN, IEEE 802.1p - Class of Service, IEEE 802.1D - Spanning Tree, IEEE 802.1w - Rapid Spanning Tree, IEEE 802.1s - Multiple Spanning Tree, IEEE 802.3ad - Link Aggregation Control Protocol (LACP), IEEE802.1v - Protocol VLAN, IEEE 802.1AB - LLDP (Link Layer Discovery Protocol), IEEE 802.1X - Access Control
Interface:	Number of Port: 50 10/100/1000Base RJ-45 Port : 48, Auto-negotiation, Auto MDI/MDIX 10G SFP+ : 2
Performance	Switching Capacity: 136G bps MAC Address Table Size: 64K Forwarding Rate: 10G port – 14,880,000pps 1000Mbps port - 1,488,000pps 100Mbps port - 148,800pps 10Mbps port - 14,880pps Packet Buffer: 64Mb
QoS Features	Number of Priority queue: 8 queues/ port Scheduling for priority queue : WRR/Strict Priority schedu- ling/Hybrid CoS : 802.1p/ IP Precedence/ IP TOS Precedence IP DSCP/ Port based Priority Rate Limiting: Ingress/Egress: 1Kbps/ 1pps granularity DiffServ (RFC2474) remarking



Technical Specifications

PoE Features	<p>802.3af/at Compliant Max. Power Output Per Port: 30W Power Consumption : 400W Current Sharing Internal Power: Built-in Power Supply PD Classification Power Management: Enable/Disable per-port Priority Setting per-port Overloading Protection per-port Power Level Setting per-port</p>
L2 Features	<p>Flow Control: 802.3x (Full-duplex)ort/ Back-Pressure (Half-duplex) Spanning Tree: IEEE 802.1D-2004(Includes IEEE 802.1w): Rapid Spanning Tree Protocol 802.1s Multiple Spanning Tree Protocol Loop Detection VLAN: IEEE 802.1Q Tagged Based, Max. VLAN Group: 4K QinQ Port-based VLAN Voice VLAN Private VLAN MVR MAC-Based VLAN Protocol-Based VAN Link Aggregation: IEEE 802.3ad with LACP: 26 trunks/ up to 8 port per trunk Static Trunk: 26 trunks/ up to 8 port per trunk Max. Group:26 Max. Ports/Group:8 IGMP Snooping: IGMP Snooping v1/v2/v3 IPv6 MLD Snooping v1/v2 Queries support/ IGMP Filtering, IGMP Leave Proxy, Immediate Leave Storm Control: Broadcast/ Multi-cast/ Un-known Unicast Jumbo Frame Support: 10K</p>



Technical Specifications

Management:	<p>Command Line Interface (CLI) Web Based Management Telnet Access Management Filtering: SNMP/ WEB/SSH/TELNET/ SNMP: v1/v2c/v3 RMON: RMON (1,2,3, & 9 groups) DHCP: Client/ Relay/ Option82/ Snooping Event/Error Log: Local Flash/ Remote Server Software Download/ Upgrade: HTTP Configuration Download / Upload sFlow Port Mirroring: One to One/ Many to One Remote Ping NTP/LLDP UPnP EEE Configuration Cable Diagnostics IPv6 Configuration</p>
Security:	<p>User Name / Password Protection User Privilege: up to 15 levels IEEE 802.1x: Port-based Access Control IP Source Guard MAC Based Authentication Web-based Authentication HTTPS SSHv2 RADIUS: Authentication/ Accounting TACACS+: Authentication ACL (Access control list)</p>
Housing:	19" Metallgehäuse, Montagewinkel beiliegend
Fan/Cooling:	3x Fans 40x40x10mm = 500W Total Consumption
Maße:	Breite/Tiefe/Höhe: 440 x 331x 44 mm Gewicht: 4,97 kg
Operating Temperature & Humidity:	0~40° 5~90% (non condensing)
Marks:	CE, ROHS
Power Input	100-240VAC