

# IPC-612 Full HD Resolution IR Bullet Network Camera



## FEATURES

- H.264 main profile compression
- Support Dual stream
- Support connection with HVR/NVR, Compatible with ONVIF(version 2) standard
- POE (optional)

MODEL: IPC-612	
Image Sensor	1/2.8"SONY IMX122 CMOS Sensor
Min illumination	Color 0.01Lux @ (F1.2, AGC ON), 0 LUX with IR B/W:0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Electronic shutter	1/50(1/60)s~1/100,000 s
D/N	Support IR-CUT
Lens	6-22MM +ICR
IR Illumination	3 x IR Dot matrix (30m)
Compression	
Video compression	H.264 Main Profile, JPEG capture
Video Bite Rate	32Kbps~6Mbps
Image	
Max Resolution	1920*1080
Frame Rate	50Hz:25fps (1920*1080) 60Hz:30fps (1920*1080)
Image settings	Saturation, Brightness, Contrast adjustable through Client software or web server
Network Function	
Storage	network storage
Intelligent Alarm	Motion detect, video loss ,network disconnection, IP address conflict, storage full, storage error
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE, SMTP,NTP(HTTPS,SIP ,802.1x,IPv6 optional)
Basic	Anti-flicker, dual stream, heartbeat, password protection
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
General	
Operating condition	-10°C~60°C, humidity 90% less (non-condensing)
Power supply	DC12V±10%, POE (optional)
Power consumption	5.5W MAX;
Dimension	335mm(L) x 103MM(W) x 96(H)