

## HNR-4418 / HNR8418 H.264 Pentaplex Standalone POE NVR



	Model	HNR-4418	HNR-8418	
IP Camera Input	Input IP CAM PORT(4ch)	4 x RJ45 camera input port	4x RJ45 camera input port	
	Embedded Ethernet Switch	Yes (IEEE 802.11a/b/g/n)		
	Embedded PoE Switch	Yes (IEEE 802.3af )		
	Resolution	VGA/D1/960H/960p/1080p		
	Protocol	Onvif v2.2 base		
Monitor Output	HD Video Output	VGA, HDMI		
	Main Video Resolution	Up to 1920x1080p		
	Screen Split Mode	1/4	1/4/6/8/9	
	PIP and Zoom	Yes		
	Audio Output	1 x RCA		
	Pentaplex Mode	Simultaneous Live, Recording, Playback, Backup, Network		
	Mobile phone support	App for Android and iOS		
Recording	Frame Rate	Adjustable frame rate for each camera		
	Recording Ways	Manual, Schedule, Event (motion, sensor), Network driven		
	Recording FPS	4ch x 30fps@ 1080p (4Mbps)	8ch x 30fps@ 1080p (4Mbps)	
	Protect Video / Audio File	Protect Video / Audio from HDD Overwrite		
	Still Image Capture	Live or Playback Image Local Capture and Backup for legal evidence		
	Internal Hard Drive	SATA, Up to 2 x HDDs		
	External Hard Drive	E-Sata		

# HNR-4418 / HNR8418

## H.264 Pentaplex Standalone POE NVR

Model		HNR-4418	HNR-8418
Remote Monitoring / Control		Remote View and Control via Gigabit Ethernet	
		Dynamic / Static / Zero Config Support	
		Web Viewer and VMS Support	
		NAT Traversal Support	
		Dual Streaming for Live and Recording	
Playback	Playback Screen Mode	E-Map support	
	Search Mode	Full, Quad	
Alarm Control	External Sensor Input	Date/Time, Calendar, Event, Motion, Protect, Capture, VCA, Text	
	Alarm Output	4CH NC / NO	
	Data Backup	Buzzer, OSD, 4 x Relay	
Others	Video Content Analysis	2x USB 2.0 Flash Memory	
	POS / ATM	AVI Format for Easy Viewing, Private Format for Image Authentication	
	NTP Server / Client	Yes (with specific cameras)	
	System Keyboard	Yes (with VSI/VSSI-Pro)	
	Printer	Yes	
	Control	Support	
	Event Log & Pre-Alarm Record	USB or Network Printer	
	Auto Deletion	IR Remote Control, USB Mouse, Client software	
	Languages	System/Event Log management, Pre-recording for Motion/Sensor	
	Power Supply	Setup Recording Duration Per Channel	
	Dimensions	48 Languages Support	
		DC 48V / 3.1A	
		272 x 265 x 85 mm (10.7 x 10.4 x 3.5 inch)	

